

Gewindedurchmesser 5,5 mm
Thread diameter 5.5 mm



ISR 25

Zylinderblechschraube

Mit ISR 25 Kopf ähnlich DIN 912, mit kurzer Spitze und Schneidkante, gleitbeschichtet

Socket head self-tapping screw

With star head 25, head similar to DIN 912, with short tip and cutting tip, anti-friction coated

Abmessungen Dimensions	Art.-Nr. Art. No.	Material Material	
ST 5,5 x 21	205 842	INOX A4	100
ST 5,5 x 23	205 895		
ST 5,5 x 25	205 896		
ST 5,5 x 27	205 897		
ST 5,5 x 29	205 898		
ST 5,5 x 31	205 899		
ST 5,5 x 33	205 900		
ST 5,5 x 35	205 901		
ST 5,5 x 37	205 843		
ST 5,5 x 39	205 902		
ST 5,5 x 41	205 844		
ST 5,5 x 43	205 903		
ST 5,5 [] x 45	205 845		
ST 5,5 x 47	205 904		
ST 5,5 x 49	205 905		
ST [] 5,5 x 51	205 846		
ST 5,5 x 53	205 906		
ST 5,5 x 55	205 907		
ST 5,5 x 57	205 847		
ST 5,5 x 59	205 908		
ST 5,5 x 61	205 909		
ST 5,5 x 63	205 848		
ST 5,5 x 65	225 050		
ST 5,5 x 69	225 138		
ST 5,5 x 75	225 139		



ISR 25

Zylinderblechschraube

Mit ISR 25, Kopf ähnlich DIN 912, mit Schneidkante, gleitbeschichtet, zu verschrauben mit Bit 299 379

Socket head s/t screw

With star-head 25, head similar to DIN 912, with cutting tip, anti-friction coated, screw in using bit 299 379

Abmessungen Dimensions	Art.-Nr. Art. No.	Material Material	
ST 5,5 x 30	205 734	INOX A4	100
ST 5,5 x 38	205 735		



ISR 25

Sonderblechschraube

Mit ISR 25, mit kurzer Spitze und Schneidkante, spezial-gleitbeschichtet, zu verschrauben mit Bit 299 379

Special self-tapping screw

With star-head 25, with short tip and cutting tip, with special anti-friction coating, screw in using bit 299 379

Abmessungen Dimensions	Art.-Nr. Art. No.	Material Material	
ST 5,5 x 24	205 922	INOX A2	100
ST 5,5 x 28	205 923		
ST 5,5 x 30	225 026		
ST 5,5 x 32	205 924		
ST 5,5 x 34	225 027		
ST 5,5 x 36	225 028		
ST 5,5 x 38	205 925		
ST 5,5 x 40	225 029		
ST 5,5 x 42	225 030		
ST 5,5 x 44	205 926		
ST 5,5 x 50	205 927		
ST 5,5 x 56,5	225 132		